V 12 GA

Alkaline Manganese

Data Sheet

Type Number:	4278
Designation IEC:	LR 43
System:	Manganese dioxide / Zinc / KOH - Electrolyte
Nominal Voltage [V]:	1,5
Typical Capacity C [mAh]:	80
Load 5.6 kOhm, at 20 °C down to 1.2 V	
Weight, approx [g]:	1,35
Volume [ccm]:	0,39
Coding:	Manufacturing Month/Year by Letter Code



Temperature Ranges [°C]:	**min.**	**max.**
Storage:	-10	65
Discharge:	-10	65
Dimensions [mm]:	**min.**	**max.**
Diameter :	11,25	11,6
Height [A/B]:	3,8	4,2

Segment:	Electronic
Main Applications:	Watch Photo Electronics Devices

Typical Capacities (at 20° C):

Discharge Type:	**Load**	**End Voltage:**	**1.2 V**
Continuous	5600 Ω	Time:	328 h
24h/d,7d/w		Capacity [mAh]:	80
Current [µA]: 270		Energy [mWh]:	108

VARTA Gerätebatterie GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst
Tel.: (+49) 7961/83-0, Telefax: (+49) 7961/83-553

Subject to change without prior notice!

Date of Issue : 23.08.1999