

SPECIFICATION



ER14250H 3.6V

Electrical characteristics

(Typical values relative to cells stored for one year at +30 °C max)

◉ Nominal capacity	1200mAh
Discharged capacity at 1mA, +25 °C, 2.0V cut off	
◉ Nominal voltage	3.6V
◉ Max. recommended continuous current	20mA
Discharged to 2.0V at +25 °C permitting 50% of the nominal capacity to be achieved	
◉ Max. Pulse capability	50mA
50mA, 0.1 second pulses every 2 minutes, drained with 50%, at 25 °C from undischarged cells with 20uA based current, yield voltage readings above 2.7V, the value may vary according to the pulse characteristics, the temperature and the cell's previous history.	
◉ Operating temperature rang	-55 °C ~ +85 °C

STORAGE:


Stored in clean, dry and cool circumstances (the temperature should be 20 degrees or lower, less than 30 degrees)

WARNING:

Don't charge, crush, disassemble, expose contents to water, heat above 100 °C or may lead to explosion, burn or poison goods leakage. Discarded battery should be buried deeply to the ground.

Key features

- High and stable operating voltage
- Long shelf life
- Annual self-discharge rate lower than 1% at +25 °C
- Long operating life
- High energy density (700wh/kg)
- Wide operating temperature rang
- Stainless steel can and cover
- Hermetic glass-to-metal sealing
- Non-flammable electrolyte
- Compliant with IEC 86-4 safety standard
- Non-restricted for transport

 UL Component Recognition
File Number MH46165



Main applications

- Public instrument
- Alarms or security equipment
- Memory backup
- GPS tracking
- Car electronics
- Professional electronic equipment
- Real time clock


.....

ER14250H 1200mAh

Discharge characteristics at 25°C




Voltage vs Temperature curve




Dimensions in mm
Weight: 9g

Available Terminations	
-/P*	Axial pin
-/T /PT2*	Radial Pin
-/PT /TP*	Polarized Tab
(*) : Reference to Standard Terminals for Single Cells	

Capacity vs Current curve (cut off with 2.0V)



Discharge characteristics after storage



Data in this page is subject to change without notice and becomes contractual only after written confirmation by Fanso.

WUHAN FANSO TECHNOLOGY CO.,LTD.

Address: Rd.5, Sitai Industrial Park, YongFeng Avenue, Hanyang District, Wuhan City, China.

Tel: +86-27-84458099

Fax: +86-27-84453116

Post Code: 430051

Http://www.fansobattery.com

E-mail: marsha@fansobattery.com or overseas@fansobattery.com